


OPEN NETWORKING
FOUNDATION

Core Information Model (CoreModel)

TR-512.3 Foundation (Identifiers and naming)

Version 1.2
September 20, 2016



ONF Document Type: Technical Recommendation
ONF Document Name: Core Information Model version 1.2

Disclaimer

THIS SPECIFICATION IS PROVIDED "AS IS" WITH NO WARRANTIES WHATSOEVER, INCLUDING ANY WARRANTY OF MERCHANTABILITY, NONINFRINGEMENT, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY WARRANTY OTHERWISE ARISING OUT OF ANY PROPOSAL, SPECIFICATION OR SAMPLE.

Any marks and brands contained herein are the property of their respective owners.

Open Networking Foundation
2275 E. Bayshore Road, Suite 103, Palo Alto, CA 94303
www.opennetworking.org

©2016 Open Networking Foundation. All rights reserved.

Open Networking Foundation, the ONF symbol, and OpenFlow are registered trademarks of the Open Networking Foundation, in the United States and/or in other countries. All other brands, products, or service names are or may be trademarks or service marks of, and are used to identify, products or services of their respective owners.

Table of Contents

Disclaimer	2
Open Networking Foundation	2
Document History	4
1 Introduction	5
1.1 References	5
1.2 Definitions	5
1.3 Conventions	5
1.4 Viewing UML diagrams	5
1.5 Understanding the figures	5
2 Introduction to the Foundation Model	5
3 CoreFoundationModel	6
3.1 Naming and identifiers	6
3.1.1 Key considerations	6
3.1.2 Classes and attributes	8
3.1.2.1 Address	8
3.1.2.2 ConditionalPackage	9
3.1.2.3 Extension	9
3.1.2.4 GlobalClass	9
3.1.2.5 Label	10
3.1.2.6 LocalClass	10
3.1.2.7 Name	11
3.1.2.8 NameAndValueAuthority	11
3.1.2.9 UniversalIdAuthority	12
3.1.3 DataTypes	12
3.1.3.1 Address	12
3.1.3.2 AddressElement	13
3.1.3.3 LocalIdAndClass	13
3.1.3.4 NameAndClass	14
3.1.3.5 NameAndValue	14
3.1.3.6 UniversalId	15
3.1.4 Use of names, identifiers and addresses	15
3.2 States	16
3.2.1 Classes and attributes	17
3.2.1.1 State_Pac	17

3.2.2 Relationship between states in Provider context..... 18
 3.2.3 Relationship between states in the client and provider context 18
 3.2.4 Use of states..... 18

List of Figures

Figure 3-1 Class Diagram for Naming and Identifier of Objects 8
 Figure 3-2 Sketch of names, identifiers and addresses for various entities 16
 Figure 3-3 States for all Objects 17

Document History

Version	Date	Description of Change
1.0	March 30, 2015	Initial version of the base document of the "Core Information Model" fragment of the ONF Common Information Model (ONF-CIM).
1.1	November 24, 2015	Version 1.1
1.2	September 20, 2016	Version 1.2 [Note Version 1.1 was a single document whereas 1.2 is broken into a number of separate parts]

1 Introduction

This document is an addendum to the TR-512_v1.2 ONF Core Information Model and forms part of the description of the ONF-CIM. For general overview material and references to the other parts refer to [TR-512.1 ONF Core IM - Overview](#).

1.1 References

For a full list of references see [TR-512.1](#).

1.2 Definitions

For a full list of definition see [TR-512.1](#).

1.3 Conventions

See [TR-512.1](#) for an explanation of:

- UML conventions
- Lifecycle Stereotypes
- Diagram symbol set

1.4 Viewing UML diagrams

Some of the UML diagrams are very dense. To view them either zoom (sometimes to 400%) or open the associated image file (and zoom appropriately) or open the corresponding UML diagram via Papyrus (for each figure with a UML diagram the UML model diagram name is provided under the figure or within the figure).

1.5 Understanding the figures

Figures showing fragments of the model using standard UML symbols and also figures illustrating application of the model are provided throughout this document. Many of the application-oriented figures also provide UML class diagrams for the corresponding model fragments (see [TR-512.1](#) for diagram symbol sets). All UML diagrams depict a subset of the relationships between the classes, such as inheritance (i.e. specialization), association relationships (such as aggregation and composition), and conditional features or capabilities. Some UML diagrams also show further details of the individual classes, such as their attributes and the data types used by the attributes.

2 Introduction to the Foundation Model

The focus of this document is the parts of Core Foundation Model of the ONF-CIM that deal with naming and identifiers.

The CoreFoundationModel covers all aspects of naming and addressing for all classes in the ONF-CIM. The focus of this document is:

- Definition of terminology related to naming and identity
- Description of the model for naming and identifiers that is inherited by other models
- Description of the state model

A data dictionary that sets out the details of all classes, data types and attributes is also provided ([TR-512.8](#)).

3 CoreFoundationModel

This Model includes all aspect of the core that are relevant to all other parts of the ONF CIM such as identifiers, naming and states.

3.1 Naming and identifiers

3.1.1 Key considerations

To communicate about a thing it is necessary to have some way of referring to that thing, i.e., to have some reference. Terms such as name and identifier are often used when describing the reference. Unfortunately these terms in general usage have ambiguity in their definition that leads to erroneous system behavior. To ensure that the controller system behavior is not erroneous, the model will adopt the following principal definitions:

- Entity¹: Has identity, defined boundary, properties, functionality and lifecycle in a global context.
 - Examples: A Equipment (see [TR-512.6 ONF Core IM - Physical](#)), an LTP (see [TR-512.2 ONF Core IM – Forwarding and Termination](#))
- Entity Feature²: An inseparable, externally distinguishable part of an entity.
 - Examples: A pin in connector (see [TR-512.6 ONF Core IM - Physical](#)), the ports of a FC (see [TR-512.2 ONF Core IM – Forwarding and Termination](#)), a face of a cube, the handle of a cup.
 - Note that this is important from a modeling perspective as the representation appears similar to that of an Entity
 - Represented using a UML class
- Role: A specific structure of responsibilities, knowledge, skills, and attitudes in the context of some activity or greater structure. The role has an identity and identifier.
- Identifier: A property of an entity/role with a value that is unique within an identifier space, where the identifier space is itself globally unique, and immutable. An identifier carries no semantics with respect to the purpose or state of the entity.
- Universally Unique Identifier³ (UUID): An identifier that is universally unique.
- Local ID: An identifier that is unique in the context of some scope that is less than the global scope.

¹ An Entity is represented using a UML class

² A Feature of an Entity is represented using a UML class

³ The term GUID was used in the previous version of the model. The change is in recognition of the more generally applicability of UUID

- Name: A property of an entity with a value that is unique in some namespace but may change during the life of the entity. A name carries no semantics with respect to the purpose of the entity.
- Label: A property of an entity with a value that is not expected to be unique and is allowed to change. A label carries no semantics with respect to the purpose of the entity and has no effect on the entity behavior or state.
 - A label can be used to carry a freeform text string for any operator purpose. The contents of a label in one view may happen to be the value of a name or identifier in another view. From the perspective of the view with the label there is no expectation other than the value is a string.
- Place: Where something is located
- Address: A structure of named values⁴ in some address space that defines a location (a volume in that address space) where the structure is a nested hierarchy.
 - A named value may be a name or identifier, the name of the value may be a name or identifier
- Route: the way (via specified intermediate locations and paths) to get to one location from another.
- Property: A quality associated with a thing, structure or location.
- Semantics: Meaning.
- Reference: Data in a communication between two applications that allows a shared understanding of the individual things.
 - This could be an identifier (including a UUID), a name, an address, or a route, depending upon the needs

Note:

- An entity may be known to be at a place in some functional or physical structure.
- A role may be known to be at a place in some process or behavioral structure.

The figure below illustrates the naming/identifier-related attributes defined in the ONF-CIM. They are Universally Unique ID (UUID), Local ID, Name and Label.


The model includes two abstract classes that provide names and identifiers, the `GlobalClass` and the `LocalClass`.⁵ A `GlobalClass` represents a type of thing that has instances which can exist in their own right (independently of any others). A `LocalClass` represents a type of thing that is inseparable from a `GlobalClass`, but that is a distinct feature of that `GlobalClass` such that the instances of `LocalClass` are able to have associations with other instances. The mandatory `LocalId` of the `LocalClass` instance is unique in the context of the `GlobalClass` instance, from which it is inseparable.

The model also includes `Extension` which is not related to naming/identification. `Extension` provides an opportunity to define properties not declared in the class that extend the class enabling a realization with simple ad-hoc extension of standard classes to be conformant.

⁴ A named value is simply a tuple with two terms, one being a value and the other being the name of that value. For example in a street address a value may be “London” and the name of that value would be “City”.

⁵ The model also provides `ConditionalPackage` to supply names and identifiers to `_Pac` classes but this is currently experimental.

Note that a UUID is applicable only to global type object classes (i.e., subclass of GlobalClass) that their instances can exist on their own right, e.g., LTP, FD, Link, FC, and NetworkElement. The other naming/identifier-related attributes are applicable to both global type object classes and local type object classes (i.e., subclass of LocalClass).⁶



CoreModel diagram: Foundation-CommonPackagesNoNotes

Figure 3-1 Class Diagram for Naming and Identifier of Objects

3.1.2 Classes and attributes

3.1.2.1 Address

Qualified Name:

CoreModel::CoreFoundationModel::SuperClassesAndCommonPackages::ObjectClasses::Address

Provides an opportunity to state the location of the entity via one or more hierarchies of narrowing contexts.

This class is abstract.

Table 1: Attributes for Address

Attribute Name	Lifecycle Stereotype (empty = Mature)	Description
address	Experimental	One or more descriptions of the location.

⁶ The intention is that only classes from the Core Model are shown in the figure. The classes shown are essentially illustrative. There is another figure in the model that captures Core Model inheritance in detail. All classes from all fragments should inherit from GlobalClass, LocalClass or ConditionalPackage. There is no issue with model dependency as the inheritance association is maintained with the class that is inheriting properties. Although not mandatory, it would seem advisable to maintain a figure per fragment that shows all classes from that fragment and their inheritance.

3.1.2.2 ConditionalPackage

Qualified Name:

CoreModel::CoreFoundationModel::SuperClassesAndCommonPackages::ObjectClasses::ConditionalPackage

The base class for conditional packages.

This class is abstract.

Inherits properties from:

- Label
- Extension

This class is Experimental.

3.1.2.3 Extension

Qualified Name:

CoreModel::CoreFoundationModel::SuperClassesAndCommonPackages::ObjectClasses::Extension

Extension provides an opportunity to define properties not declared in the class that extend the class enabling a realization with simple ad-hoc extension of standard classes to be conformant.

This class is abstract.

Table 2: Attributes for Extension

Attribute Name	Lifecycle Stereotype (empty = Mature)	Description
extension		List of simple name-value extensions.

3.1.2.4 GlobalClass

Qualified Name:

CoreModel::CoreFoundationModel::SuperClassesAndCommonPackages::ObjectClasses::GlobalClass

Represents a type of thing (an Entity) that has instances which can exist in their own right (independently of any others). Entity: Has identity, defined boundary, properties, functionality and lifecycle in a global context. (consider in the context of a Class: (usage) The representation of a thing that may be an entity or an inseparable Entity Feature).

This class is abstract.

Inherits properties from:

- Address

- State_Pac
- Label
- Extension
- Name

Table 3: Attributes for GlobalClass

Attribute Name	Lifecycle Stereotype (empty = Mature)	Description
localId		An identifier that is unique in the context of some scope that is less than the global scope. (consider in the context of Identifier: A property of an entity/role with a value that is unique within an identifier space, where the identifier space is itself unique, and immutable. The identifier therefore represents the identity of the entity/role. An identifier carries no semantics with respect to the purpose of the entity.)
uuid		UUID: An identifier that is universally unique (consider in the context of Identifier: A property of an entity/role with a value that is unique within an identifier space, where the identifier space is itself globally unique, and immutable. An identifier carries no semantics with respect to the purpose or state of the entity) The uuid should be treated as opaque by the user.

3.1.2.5 Label

Qualified Name:

CoreModel::CoreFoundationModel::SuperClassesAndCommonPackages::ObjectClasses::Label

A property of an entity with a value that is not expected to be unique and is allowed to change. A label carries no semantics with respect to the purpose of the entity and has no effect on the entity behavior or state.

This class is abstract.

Table 4: Attributes for Label

Attribute Name	Lifecycle Stereotype (empty = Mature)	Description
label		List of labels.

3.1.2.6 LocalClass

Qualified Name:

CoreModel::CoreFoundationModel::SuperClassesAndCommonPackages::ObjectClasses::LocalClass

A LocalClass represents a Feature of an Entity. It is inseparable from a GlobalClass but is a distinct feature of that GlobalClass such that the instances of LocalClass are able to have associations to other instances.. Feature of an Entity: An inseparable, externally distinguishable part of an entity. The mandatory LocalId of the LocalClass instance is unique in the context of

the GlobalClass from which it is inseparable. (consider in the context of a Class: (usage) The representation of a thing that may be an entity or an inseparable feature of an entity)

This class is abstract.

Inherits properties from:

- Address
- State_Pac
- Label
- Extension
- Name

Table 5: Attributes for LocalClass

Attribute Name	Lifecycle Stereotype (empty = Mature)	Description
localId		An identifier that is unique in the context of some scope that is less than the global scope. (consider in the context of Identifier: A property of an entity/role with a value that is unique within an identifier space, where the identifier space is itself unique, and immutable. The identifier therefore represents the identity of the entity/role. An identifier carries no semantics with respect to the purpose of the entity.)

3.1.2.7 Name

Qualified Name:

CoreModel::CoreFoundationModel::SuperClassesAndCommonPackages::ObjectClasses::Name

Name: A property of an entity with a value that is unique in some namespace but may change during the life of the entity. A name carries no semantics with respect to the purpose of the entity.

This class is abstract.

Table 6: Attributes for Name

Attribute Name	Lifecycle Stereotype (empty = Mature)	Description
name		List of names.

3.1.2.8 NameAndValueAuthority

Qualified Name:

CoreModel::CoreFoundationModel::SuperClassesAndCommonPackages::ObjectClasses::NameAndValueAuthority

Represents the authority that controls the legal values for the names and values of a name/value attribute.

This class is abstract.

This class is Preliminary.

Table 7: Attributes for NameAndValueAuthority

Attribute Name	Lifecycle Stereotype (empty = Mature)	Description
uuid		The UUID for the NameValueAuthority.

3.1.2.9 UniversalIdAuthority

Qualified Name:

CoreModel::CoreFoundationModel::SuperClassesAndCommonPackages::ObjectClasses::UniversalIdAuthority

Represents the authority that controls the allocation of UUIDs.

This class is abstract.

This class is Preliminary.

Table 8: Attributes for UniversalIdAuthority

Attribute Name	Lifecycle Stereotype (empty = Mature)	Description
uuid		The UUID for the UUID authority.

3.1.3 DataTypes

3.1.3.1 Address

Qualified Name:

CoreModel::CoreFoundationModel::SuperClassesAndCommonPackages::TypeDefinitions::Address

A description of location via a hierarchy of narrowing contexts.

Table 9: Attributes for Address

Attribute Name	Lifecycle Stereotype (empty = Mature)	Description
addressName	Experimental	The name of the address (to allow the specific hierarchy to be distinguished from others for the same entity).
addressElement	Experimental	The elements of the address that form the recursive scope narrowing.

3.1.3.2 AddressElement

Qualified Name:

CoreModel::CoreFoundationModel::SuperClassesAndCommonPackages::TypeDefinitions::AddressElement

One element of a hierarchy of elements. Note that the element must have one and only one value chosen from a list of potential value types.

Table 10: Attributes for AddressElement

Attribute Name	Lifecycle Stereotype (empty = Mature)	Description
addressElementName		The name of the address element (e.g. "shelf" as an element of a shelf/slot/port addressing scheme). The remainder of the structure has the reference for the shelf.
localId		If the element is a localId (where the element above in the hierarchy must be the context in which the specific localId is relevant).
uuid		If the element is a uuid (where this element could be the top of a hierarchy but may also be at some level in the hierarchy where address navigation is considered necessary to assist in location of the UUID).
name		If the element is a name.
_address		See referenced class
arbitraryElement		Where the element is from some external model that is not formally represented in this model.

3.1.3.3 LocalIdAndClass

Qualified Name:

CoreModel::CoreFoundationModel::SuperClassesAndCommonPackages::TypeDefinitions::LocalIdAndClass

The localId and the class of entity that it identifies.

Table 11: Attributes for LocalIdAndClass

Attribute Name	Lifecycle Stereotype (empty = Mature)	Description
classOfInstance	Experimental	The class to which the name refers.

Attribute Name	Lifecycle Stereotype (empty = Mature)	Description
localId	Experimental	The localId of the entity.

3.1.3.4 NameAndClass

Qualified Name:

CoreModel::CoreFoundationModel::SuperClassesAndCommonPackages::TypeDefinitions::NameAndClass

The name and the class of entity that it names.

Table 12: Attributes for NameAndClass

Attribute Name	Lifecycle Stereotype (empty = Mature)	Description
classOfInstance	Experimental	The class to which the name refers.
name	Experimental	If the element is a name.

3.1.3.5 NameAndValue

Qualified Name:

CoreModel::CoreFoundationModel::SuperClassesAndCommonPackages::TypeDefinitions::NameAndValue

A scoped name-value pair.

Table 13: Attributes for NameAndValue

Attribute Name	Lifecycle Stereotype (empty = Mature)	Description
valueName		The name of the value. The value need not have a name.
value		The value.
_nameAndValueAuthority		The authority that defines the named value.
_globalClass		The scope of the name uniqueness.
_localClass		The scope of the name uniqueness.

3.1.3.6 *UniversalId*

Qualified Name:

CoreModel::CoreFoundationModel::SuperClassesAndCommonPackages::TypeDefinitions::UniversalId

The universal ID value where the mechanism for generation is defined by some authority not directly referenced in the structure. A example structure is [IETF RFC4122].

Table 14: Attributes for UniversalId

Attribute Name	Lifecycle Stereotype (empty = Mature)	Description
value		The specific value of the universal id.

3.1.4 Use of names, identifiers and addresses

The following figure provides various examples of naming and identifier. The figure is currently under development. The figure includes diagram element from [TR-512.5 ONF Core IM - Resilience](#) and [TR-512.6 ONF Core IM Physical](#).





Figure 3-2 Sketch of names, identifiers and addresses for various entities

3.2 States

The Core Foundation Model also defines a State_Pac artifact, which provides state attributes. The work on states is preliminary at this stage (it is derived from [ITU-T X.731]). The State_Pac is inherited by GlobalClass and LocalClass object classes. The use of these states provides a consistent way represent the overall operability, usability and current usage of the resource.

It should be noted that the states are «Preliminary»/«Experimental».



CoreModel diagram: GeneralizedStates

Figure 3-3 States for all Objects

3.2.1 Classes and attributes

3.2.1.1 State_Pac

Qualified Name: CoreModel::CoreFoundationModel::StateModel::ObjectClasses::State_Pac

Provides general state attributes.

This class is abstract.

This class is Preliminary.

Table 15: Attributes for State_Pac

Attribute Name	Lifecycle Stereotype (empty = Mature)	Description
operationalState	Preliminary	The operational state is used to indicate whether or not the resource is installed and working.
administrativeControl	Experimental	The administrativeControl state provides control of the availability of specific resources without modification to the provisioning of those resources. The value is the current control target. The actual administrativeState may or may not be at target.
adminisatraveState	Preliminary	Shows whether or not the client has permission to use or has a prohibition against using the resource. The administrative state expresses usage permissions for specific resources without modification to the provisioning of those resources.

Attribute Name	Lifecycle Stereotype (empty = Mature)	Description
lifecycleState	Preliminary	Used to track the planned deployment, allocation to clients and withdrawal of resources.

3.2.2 Relationship between states in Provider context

If the lifecycleState is PLANNED then the operationalState must be DISABLED and the administrativeState should be LOCKED.

In all other circumstances the states are independent.

3.2.3 Relationship between states in the client and provider context

The table below lists the states in the provider context that influence the states in the client context. The client does not have direct visibility of the provider states but does perceive effect through the operationalState.

Provider State	Value	Client State	Value
operationalState	DISABLED	operationalState	DISABLED
administrativeState	LOCKED	operationalState	DISABLED
lifecycleState	PLANNED	operationalState	DISABLED

Table 16: Influence of Provider state on Client state

No other states in the client context have a dependency on the state in the provider context.

None of the states in the client context influence the states in the provider context.

The administrativeState in the provider context is not visible in the client context. The client context may maintain an independent administrativeState.

The provider controls the lifecycleState that is visible to the client context.

3.2.4 Use of states

Examples to be added

End of document